



Setting the Standards

OTO (Optical Termination Outlet)



Description	Fiber Optic Termination Outlet (OTO) great for jointing fiber cable and pigtails, It protects fiber optic splices and enables distribution. The termination box is wall-mounting and is mainly used in telecommunication and network equipment rooms.
Features and Benefits	<ol style="list-style-type: none"> 1. Small and light-weight 2. Reliable and durable 3. Easy installation 4. Easy click-in cover mounting 5. Fixing pin for splice protection sleeve 6. Simple maintenance
Applications	<ul style="list-style-type: none"> ● FTTH ● Data centers, premise installations and telecommunication networks ● Ethernet, fiber channel, ATM, LAN, MAN and WAN ● Data communication ● Indoor applications
Certification and Compliance	<p>RoHS</p> <hr/> <p>UL 94</p> <hr/> <p>TIA/EIA 568.C</p> <hr/> <p>ISO/IEC 11801, EN50173, IEC60304, IEC61754, EN297-1</p>

OTO (Optical Termination Outlet)



Ordering Information	Description	Part Number
	Optical Termination Outlet (OTO)	OXIN-5910
Packaging	Description	
	Clear poly bag, 1 pc per bag	
Physical Characteristics	Parameter	Value
	Material	ABS
	Colour	White
	Suitable for adaptor type	SC sx / square-type FC/ST sx / LC Duplex
	Number of fibers	4
	Number of ports	2
	Accessories	Screw*2
	Net Weight	50 g
Dimensions	86mm x 86mm x 23mm	
Mechanical Characteristics	Parameter	Value
	Operating temperature	-40 ~ 65°C
	IP rating	IP52