## Product Data Sheet OTS-6000



Setting the Standards

## **Optical Talk Set**



Description	Oxin Optical Talk Set, OTS-6000, is an intelligent and efficient instrument that combines in one set the functions of both a digital optical phone and a stabilized light source. It is widely used in operations of installation, optical testing, maintenance and fiber attenuation value testing in data network, CATV and Telecommunication network. The OTS-6000 Talk Set can carry out full-duplex communication with high quality connection and not be affected by distance.		
	1.	Full-duplex digital communication with high quality conversation connection and low background noise	
Features	2.	Together with Optical Clip-on Coupler, enables on line communications available	
and	3.	Combining functions of both a digital optical phone call and a stabilized light source.	
Benefits	4.	Large LCD display with backlight	
	5.	Low battery power indication	
Applications	٠	Maintenance in Telecom	
	•	Maintenance CATV	
	•	Fiber Optic Lab Testing	
	•	Other Fiber Optic Measurements	

## **Optical Talk Set**



Ordering	Description	Part Number	
Information	Optical Talk Set	OTS-6000	
Packaging -	Description		
Fackaging -	Cardboard box, 1 unit per box		
Standard -	Description		
Accessories	Optical Talk Set (pair), Protective Rubber Boot, Headset, Rechargeable battery,		
Accessories	Power Supply Adaptor, User Manual, Cotton swabs and soft carrying case		
	Parameter	Value	
_	Emitter Type	FP-LD	
	Transmission Distance	≥80km	
Technical	Dynamic Range	40dB	
Characteristics	Output Power	-5~-7dBm(125/9um), CW	
	Output Power	or 270Hz, 1KHz, 2KHz Modulation	
	Output Stability	±0.1dB/±0.25dB(8/1hrs) CW	
_	Optical Connector	FC/PC	
	Parameter	Value	
	Power Supply	Rechargeable Battery + Power Supply Adapt	
Physical <sup>–</sup> Characteristics –	Battery Operating Time	5 hours	
Characteristics –	Dimensions	215 mm x 115 mm x 55 mm	
	Weight	520 g	
	Parameter	Value	
Mechanical = Characteristics -	Operating temperature	-10 ~ 60°C	
	Storage temperature	-25 ~ 70°C	



## Oxin Group S.A.

Head-office:5, bd du General Martial Valin,<br/>75736 Paris Cedex 13 - FranceWeb:www.OxinGroup.netE-mail:info@oxingroup.net

OTS-6000 Data Sheet VER 2.2EN 2017-08-09

Copyright © 2017 Oxin Group S.A. All Rights Reserved